

Dung Distributor **K•L•E**



Technical Data

	DS 6 E	DS 9 E	DS 9T(Tandem)
Permissible laden weight	6,000 kg	8,000 kg	10,000 kg
Empty weight	2,300 kg	2,500 kg	3,000 kg
Size of platform (mm)	4,500 x 1,800	4,700 mm x 2,000 mm	
All-steel bottom	x	x	x
Platform gates	600mm	600 + 400 mm	
Capacity	approx. 5 m ³	approx. 9 m ³	
Front protection gate	x	x	x
Wheel gauge	1,700 mm	1,800 mm	
Overrunning brake with reverse gear automatism	x	x	—
Compressed-air brake system	—	—	x
Outlet of distribution unit	1,000 mm	approx. 1,200 mm	
Spiral distribution unit 4 vertical rollers	x	x	x
Hydraulic distribution roller protection	x	x	x

x = standard equipment

Oil bath drive of distribution unit
Hydraulic scraper floor drive
Forward and reverse motion of scraper floor
Scraper floor
Manganese steel scraper floor chains 12mmØ
Electric illumination
Tyres
Resilient tandem undercarriage (Boggi)
Driven by means of universal joint shaft/universal joint shaft for wide angles including safety clutch

	DS 6 E	DS 9 E	DS 9T(Tandem)
Oil bath drive of distribution unit	4	4	4
Hydraulic scraper floor drive	x	x	x
Forward and reverse motion of scraper floor	x	x	x
Scraper floor	2 chains	4 separate chains	
Manganese steel scraper floor chains 12mmØ	x	x	x
Electric illumination	x	x	x
Tyres	19.0/45 x17	500/50 x17	19/45 x17
Resilient tandem undercarriage (Boggi)	—	—	x
Driven by means of universal joint shaft/universal joint shaft for wide angles including safety clutch	x	x	x

In-house development and production according to CE standards



Richard Ostler Maschinenbau GmbH

Schlingener Straße 2a
D-87668 Rieden bei Kaufbeuren

Telephone: +49 (0) 8346/98 20 26

Telefax: +49 (0) 8346/98 20 27

e-mail: info@ostler-maschinen.de

www.ostler-maschinen.de